

IDX140 Interchangeable Heat Seal Machine



The IDX140 machine is designed to seal heat sensitive film to plastic or paper containers for a tamper evident, stay-fresh seal.

The machine operates with a mechanical seal head and interchangeable pockets using a straight or optional radius die cutter.

Standard Features

- Stainless Steel Construction
- Intermittent Motion Pocket Conveyor with Adjustable Dwell Seal Head for Superior Seals and High Production Speeds
- Variable Speed
- Universal Exit Ramp
- Removable Crumb Tray

Optional Features

- Radius Cutter
- Electric Eye for Pre-Printed Registered Lidding Films
- Adjustable Height, Locking Casters
- Custom Length Machines Available
- "Jaguar" In-Line Film Printer/Coder

Dimensions	
Side Panel Length	84" (Including Take-off Ramps)
Chain Length	140"
Width (at Loading Area).....	18-1/2"
*Overall Width	25"
*Operation Height	34" (to 37" w/adj. caster opt.)
*Overall Height	47" (to 50" w/adj. caster opt.)
Loading Area Length	Approximately 24"
Weight	500 LBS (Approximately)
Maximum Standard Container Size	7-1/2" W x 10" L x 3-1/2" D

Electrical	
Volts (with ground).....	115/120V AC, (w/Ground)
Amperes Produced	18 AMP
Electrical Receptacle AMP Rating.....	20 AMP
Watts	2160
Hz.....	60
Phase	Single