

# THE PLATINUM PACKAGING GROUP

## PPG SHRINK TUNNEL FEATURES:

A "Cool Down" Feature That Automatically Shuts The Systems Off

Lighted Chamber With Viewing Window To Monitor Shrink Performance

Variable Speed Conveyor Control

Hi - Low Speed Fan Controls

Transfer Roller To Bridge Gap Between Sealer & Tunnel

Adjustable Leg Extension With Locking Casters



**PPG Shrink Tunnels Are Available With Chamber Sizes Ranging From 12" to 20" In Height: 4', 6' & 8' In Length: 17", 22" & 30" In Width.**

## SYSTEMS SPECIFICATIONS:

Model	System Length	Shrink Chamber Dimensions			Electrical Specifications
		Length	Width	Height	
PPG1712/4	72"	48"	19"	12"	Three heaters w/fans, each with individual speed controls, 12KW, 220V, 48amps/1ph, or 28amps/ 3 ph.
PPG2212/4	72"	48"	24"	12"	
PPG3012/4	72"	48"	32"	12"	Four heater system w/fans and controls, 220V, 16KW, 50amps, 3ph
PPG1712/6	96"	72"	19"	12"	Six heaters w/fans, each with individual speed controls, 220V, 24KW, 60amps 3ph
PPG2212/6	96"	72"	24"	12"	
PPG3012/6	96"	72"	32"	12"	
PPG1712/8	120"	96"	19"	12"	Six heaters w/fans, each with individual speed controls, 220V, 24KW, 60amps 3ph
PPG2212/8	120"	96"	24"	12"	
PPG3012/8	120"	96"	32"	12"	

Conveyor Options:

Teflon Mesh Belt

Stainless Steel Belt

Hard Plastic Mesh Belt

Live Roller ( Silicone or Optional Teflon Cover)



Manufactured In The U.S.A.

**THE PLATINUM PACKAGING GROUP**

So. California Office:  
7627 Somerset Blvd.  
Paramount, CA 90723

tel: (562) 630-6700  
fax: (562) 630-6716  
email: [info@platinumpkggroup.com](mailto:info@platinumpkggroup.com)