

# THE PLATINUM PACKAGING GROUP



## “UNIVERSAL” SIDE SEAL

“Integrated” solid knife cross seal, side seal system ensures center line sealing at all times. Sealing area is protected by interlocked safety guarding.

## SIMPLE CHANGE OVER

Product change over is made extremely simple by adjustment of two crank handles to scale settings and slider type infeed. No other adjustments are necessary.



## OPERATOR COMMAND CENTER

The Operator Command Center is conveniently located and features a two line LED display with a 5 button direct access machine control for simple setup. Command Center also has 3 operational mode lights and capability of storing four product presets.



## FILM SCRAP SYSTEM

The film scrap rewind incorporates a variable speed drive allowing it to rewind today's thin gauge films. No additional power or equipment is required. The system is totally self contained.

## FILM DELIVERY SYSTEM

The Film Cradle located in the rear of the system at floor level allows for quick and easy roll changes. The air inject and adjustable pin perf systems create a controlled air escape to produce exceptional shrink performance..

## SYSTEMS SPECIFICATIONS:

MODEL	PACKAGE SIZE			MACHINE SPECIFICATIONS		
	WIDTH	HEIGHT	LENGTH	LENGTH	WIDTH	HEIGHT
PPG17	2" to 16"	to 8"	INFINITE	91"	43"	60"
PPG22	4" to 21"	to 8"	INFINITE	100"	51"	60"
PPG30	6" to 29"	to 8"	INFINITE	108"	64"	60"



Manufactured In The U.S.A.

ELECTRICAL: 120 volt, 15 amps AIR REQUIREMENTS: 1CFM @ 80 psi  
 SPEED: 0-100 fpm up to 60 p/p/m CONVEYOR HEIGHT: Adjustable 34" to 36"

THE PLATINUM PACKAGING GROUP

So. California Office:  
 7627 Somerset Blvd.  
 Paramount, CA 90723

tel: (562) 630-6700  
 fax: (562) 630-6716  
 email: info@platinumpkggroup.com