

# THE PLATINUM PACKAGING GROUP

## VB (Wash Down) Infeed Conveyor V.B.I.C

### Benefits and Features

- **SEALED STAINLESS FRAME**

Frame is tubular (not rectangular) stainless steel.  
Gauge... 3/16-inch nominal (Schedule 40) Wall.  
SS Seam welded and fully closed to protection from corrosion.  
Fitted with food-area rated urethane SS casters, swivel mounts, locks.

- **FOOTPRINT**

101.50" Length x 39.13" Height  
Raising To 61" at Drop Point  
Clear Feeding Space 48.4" / 6" Cleats

- **CONVEYOR BELT**

Width Belt is 8-1/2" Width / Usable width 6".  
Cleat Size Cleats 2" tall / 6" spacing / 6" Width

- **BELT RIDES WASH DOWN**

Special food-grade belt rides /removable bed glides  
Food-grade UHMW plastic.  
The glides key to stainless steel support posts and  
simply lift off for cleaning.

- **NO TOOLS NEEDED, FULLY WASHED DOWN.**

Edge guides laser-cut slots.  
Removal without tools. The edge guides are numbered to match  
numbers engraved in the conveyor flanges for easy reassembly.  
Edge guides removal in 1-minute, release the belt tensioner  
handle to complete the disassembly

- **GEARBOX SPECS**

The indexing conveyor uses a 400W servomotor  
High-precision gear head precise index movement.

- **POWER**

208-230V AC, single phase power with a 10A minimum supply recommended.



---

THE  
PLATINUM PACKAGING  
GROUP

So. California Office:  
7627 Somerset Blvd.  
Paramount, CA 90723

tel: (562) 630-6700  
fax: (562) 630-6716  
email: [info@platinumpkggroup.com](mailto:info@platinumpkggroup.com)