



NOTES:
 100-120 VAC MAIN POWER
 VARIABLE SPEED 0-600 INCHES PER MINUTE

TOLERANCES UNLESS OTHERWISE SPECIFIED		MATERIAL:	
.X ± 0.050 (1.27mm)	ANGULAR ± 0°30'	DRAWN BY: DTB	
.XX ± 0.020 (0.51mm)	MACH. SURF.		
.XXX ± 0.005 (0.13mm)		DATE: 3/23/2016	
INCH THREADS: CLASS 2A or 2B METRIC THREADS: CLASS 6G or 6H REMOVE BURRS AND BREAK EDGES .010 MAX (0.25mm) MACH. FILLET RADII: .020 MAX (0.51mm) MACH. SURF. FLAT WITHIN .001 IN/IN (0.01 mm/cm) OTHER SURF. FLAT WITHIN .003 IN/IN (0.03 mm/cm) DIA. ON COMMON ♀ TO BE CONCENTRIC WITHIN .005 TIR (0.13mm) PERPENDICULAR SURF. TO BE SQUARE WITHIN .002 IN/IN (0.02 mm/cm) REFERENCE DIMS HAVE NO TOLERANCES DO NOT SCALE DRAWING		SCALE:	TITLE: VERTEK JR EXIT ELEVATOR
		1:25	
		SHEET: 1 of 1	DWG NUMBER: M-68272
			Job: