# THE PLATINUM PACKAGING GROUP

# **PLAT**Machinery Horizontal Flow Wrapper

**MODEL 90** H90 H90M



### Performance Output

Units wrapped and sealed at speeds Up to 80 To 100 Pks Per Minute (Depending On Film Type & Single or 2 Up Seal Heads)

### Applications

fresh, frozen, & prepared foods produce consumer goods Style extended end seal (crimp)

#### Film Types polyester polypropylene printed or clear film perforated film

### **Technical Specifications**

## Performance Output

Up to 90 ppm based on a 6" long bag

#### Dimensions

Machine Size (Approx.)	
Length	155
Width	36
Height	62

#### Infeed Conveyor

Length	92"
Feed Space	54"
Height above floor	37"

#### Product Discharge

Conveyor	24" Standard	
	48" Optional	

Weight 900 lbs base machine

Utility Connection Electric supply 230V, 3PH, 60Hz

## **Packaging Specifications**

#### Maximum Package Size

(Not tolerated s	simultaneously)
Length	16"
Width	7"
Height	2 5/8" Standard
	3 1/2" Optional

#### Wrapping Material

Maximum	Roll	Diameter	13'
Maximum	Roll	Width	20'

Fin Seal Assembly (length seal)First setPullingSecond setSealing

End Crimper (cross seal)1-up x 8" wideStandard1-up x 10" wideOptional

## **Standard Features**


Touch screen monitor Program up to 15 products Left-to-right product flow, facing the control panel Powder coated frame Stainless steel covers Food contact approved conveyor Overload clutch on crimpers

## **Optional Features**

USDA-compliant infeed conveyor Relieved upper crimper shaft Roller rider conveyor Dual parent roll Extended infeed sections Dual pitch infeed conveyor Stainless steel frame & shafts Printer / code date interface Electric eye film registration No product – No bag No gap – No seal

# MODEL 90

Compact, Flexible package sizes Low maintenance, Easy changeover



## **Overview**

PPG's exceptionally versatile MODEL 90 wrappers are designed to minimize downtime while decreasing maintenance and increasing productivity.

Product operating parameters may be set within 15 saved files and recalled instantly for fast, accurate product changeover.

An adjustable forming box functions with a variety of products and also allows for fast product size changeover—no tools required.

The MODEL 90 is surprisingly compact, saving valuable floor space while offering 4.5 feet of unobstructed product feeding space.

A variety of roll stock materials, printed or clear films are suitable on these machines.



Adjustable Former | Easy size changeover for different products

## H90 Horizontal Flow Wrapper

Designed with independent servo motors at the infeed conveyor, fin seal wheels, and end crimper; this three-axis servo wrapper is synchronized through an advanced motion control processor.

The H90 is designed for optimum ease-of-use and flexibility. Crimper pause is determined automatically so that product phasing is quickly adjusted on-the-fly through the HMI touch screen.

## H90M Horizontal Flow Wrapper

The H90M's unique EZ-SET end crimper phasing control allows the operator to position the crimper between products during initial setup, then easily fine tune the setting—all while the machine is running. It is powered by a robust 1/2 HP AC drive motor.

## **Standard Features**

Model	Drive	PPM	Touch Screen	Food Safe	Feed Space
H90	servo	90	•	•	54"
H90M	mechanical (M)	90	•	•	54"

## **Optional Accessories**

Lazy Susan (rotary turn table) Adjustable side table Spare parts kit





Lazy Susan With Side Tables

Roll Up Or Attached Side Tables

THE PLATINUM PACKAGING GROUP tel: (562) 630-6700 • fax: (562) 630-6716 7627 Somerset Blvd., Paramount, CA 90723 sales@platinumpkggroup.com