

THE PLATINUM PACKAGING GROUP

PLAT*Machinery* Free Standing Fillers

COMPACT FILLER SERIES

3 Models for all Your Needs

The **Compact Series** of depositors are work horses and can be fitted with a full range of Unifiller accessories and attachments.

The Compact is available in four options:

- Compact Table Top FS
- Compact Mobile FS
- Compact Power Lift FS
- Dual (two Compacts on one frame)

Benefits:

- Small footprint
- Speed and portion accuracy
- Full wash down — all food contact parts dishwasher safe
- Tool free, quick cleaning and change-over design
- Deposit range — 0.25 oz (7 ml) 18 oz (530 ml)



Features:

- 5 product cylinder sizes available to meet your production requirements
- Stainless Steel design — Volumetric depositing
- Power Lift Model has a "one touch" system for raising and lowering of hopper
- The Mobile can be height adjusted manually
- Mobile and Power Lift have a 14 US Gallon (52 liter) conical hopper
- Table Top has a 6 US Gallon (23 liter) conical hopper


System Includes:

- Removable work table
- Quick start guide & spare parts kit





1. Compact Table Top
2. Compact Mobile
3. Compact Power Lift



| Product Cylinder Size | DEPOSIT VOLUME (fl oz) | | | |
|-----------------------|------------------------|---------|--------|----------|
| | Min. (15%) | | Max. | |
| 3" | 2.7 oz | (80 ml) | 18 oz | (530 ml) |
| 2.5" | 1.8 oz | (53 ml) | 12 oz | (360 ml) |
| 2" | 1.1 oz | (32 ml) | 7.6 oz | (225 ml) |
| 1.5" | 0.6 oz | (18 ml) | 4.0 oz | (120 ml) |
| 1" | 0.25 oz | (7 ml) | 1.7 oz | (50 ml) |

PERFORMANCE SPECIFICATIONS



Speed

Up to 140 deposits/min (8400 deposits/hr) based on 20% volume and product consistency.



Volume

0.25 oz to 18 oz.
7ml to 530ml



Power

Air:
4 CFM @ 80psi,
113 liters/minute @ 5.5 bar



Particle Size

Up to 3/4" cube
19mm

SHIPPING INFORMATION

Mobile / Power Lift:

- Dimensions: 36" x 30" x 52" (90 cm x 75 cm x 130 cm)
- Weight: 200 lbs. (91 kg)

Table Top:

- Dimensions: 23"x 22" x 26" (58 cm x 56 cm x 66 cm)
- Weight: 85 lbs (39 kg)

Note: Equipment quoted is designed to run at the quoted speed and is dependent on operator efficiency, skill, deposit size and product consistency.

Product Configuration

Base Machine

| | |
|--|--------------|
| | Standard |
| | NSF Standard |

Hopper

| | |
|--|--|
| | 14 US Gal Conical Heated |
| | 10 US Gal Cylindrical w Follower Plate |

Product Cylinder

Hot kits for product temperatures of 140/180 °F

| STD | Hot | Size |
|-----|-----|------|
| | NA | 1" |
| | | 1.5" |
| | | 2" |
| | | 2.5" |
| | | 3" |

Uni-Block

| | |
|--|------------------|
| | Standard |
| | Extended Version |
| | Rotary Uni-Valve |

Uni-Valve

| | |
|--|----------|
| | Standard |
| | Hot |

Notes

Attachments – Handheld Nozzles

| | |
|--|-------------------------------------|
| | Hand Held Nozzle 1" |
| | Hand Held Nozzle 1.5" |
| | Hand Held Nozzle 1.5" Rotary Cutoff |

Attachments – Fixed Nozzles

| | |
|--|-------------------------------|
| | Drip Free Nozzle 1" |
| | Spot Depositor Kit |
| | Drip Free Nozzle 1.5" |
| | Rotary Cut-Off Nozzle |
| | Twin Injection Nozzle ¼ Short |
| | Twin Injection Nozzle ¼ Long |
| | Twin Injection Nozzle ⅜ Short |
| | Twin Injection Nozzle ⅜ Long |
| | Diving Nozzle 1.5" |
| | |
| | |
| | |

Attachments - Other

| | |
|--|--|
| | |
| | |
| | |

Accessories

| | |
|--|------------------------------|
| | Photo Sensor |
| | V-Block Centering Guide |
| | Hopper Stopper |
| | Portion / Fill Kit |
| | Preventative Maintenance Kit |
| | |
| | |
| | |
| | |

THE PLATINUM PACKAGING GROUP

tel: (562) 630-6700

7627 Somerset Blvd., Paramount, CA 90723

TO PLACE ORDERS:
sales@platinumpkggroup.com

FOR MORE INFORMATION:
www.platinumpkggroup.com

QUESTIONS:
information@platinumpkggroup.com