


THE PLATINUM PACKAGING GROUP

PLAT*Machinery*

PPG *ROBO 3.0*

Intelligent Food Automation

PPG Robotic' collaborative robot system automates the manual food assembly process for ready-to-eat meals thereby helping increase yield.



Features

Flexible Deposits

- Capable of depositing varying ingredient portions* in any container, in any placement, and on any conveyor.

*less than 4 lb

Increased Product Yield

- Increase labor productivity resulting in an improved bottom line.
- Reduces material usage with less variability than human workers; resulting in greater product output.

Food-Safe Design

- Intuitive design allows for easy and efficient cleaning using low-pressure washing and COP tanks.
- Designed and manufactured in accordance with IP67 standards with food-grade stainless steel and Delrin.

Human-Safe Design

- UR5e collaborative robot arm and ISO-15066 compliant design mitigates risks and improves worker safety.

Intuitive Touchscreen Display

- Accessible human-readable text interface that's easy to follow, understand, and is clearly recognizable by users.
- Intuitive ingredient refill design decreases downtime and increases profitable uptime.
- Automated processes reduce changeover time to less than 5 minutes.

Adaptable to Existing Infrastructure

- Systems can be slotted into existing assembly lines without customization or retrofitting.

Dimensions

Width	762 mm (30.0 in.)
Depth (total)	1282.7 mm (50.5 in.)
Depth (to conveyor)	1143 mm (45.0 in.)
Height	1905 mm (75.0 in.)
Frame material	304 stainless steel

Performance

Deposits per minute	18 - 20 BPM
Number of conveyor lanes	1 per System
Deposit weight consistency	≥ 10% better (compared to a human worker)
Food product capacity	60 qts (56.8 L)
Max deposit weight	1.5 lb
Recipe changeover time	Less than 5 minutes

Facilities

Chef Systems require electrical, air, and internet connections compliant with the specifications below:

Conveyor

Conveyor height	876.3 mm (34.5 in.) - 952.5 mm (37.5 in.)
Max conveyor slope	3 degrees
Max floor slope	3 degrees

Power

Max current draw	5 A
Connection	NEMA 5-15P or NEMA L5-20R
Voltage	120 V

Compressed Air

Quality	Clean, Dry Air (CDA)
Air draw	0.5 CFM
Air pressure	100 - 130 psi
Connection	1/4in. Industrial Interchange Pneumatic Coupling

Wi-Fi

Minimum bandwidth	10 Mbps up / 10 Mbps down
Connection	Ethernet (preferred) or Wi-Fi
Data usage	~25 GB per System per day (includes downloading and uploading)

Environment

Operating temperature range	1°C - 32°C (33.8°F - 89.6°F)
Water resistance	IP67
Humidity	
Relative humidity	<90%, non-condensing

THE PLATINUM PACKAGING GROUP

tel: (562) 630-6700

7627 Somerset Blvd., Paramount, CA 90723

TO PLACE ORDERS:

sales@platinumpkggroup.com

FOR MORE INFORMATION:

www.platinumpkggroup.com

QUESTIONS:

information@platinumpkggroup.com